

### (19) World Intellectual Property **Organization** International Bureau



# 

#### (43) International Publication Date 11 March 2004 (11.03.2004)

### **PCT**

## (10) International Publication Number WO 2004/020340 A2

(51) International Patent Classification7:

C<sub>02</sub>F

(21) International Application Number:

PCT/US2003/026456

- (22) International Filing Date: 22 August 2003 (22.08.2003)
- (25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 60/406,545


28 August 2002 (28.08.2002)

- (71) Applicant (for all designated States except US): KI-NETICO INCORPORATED [US/US]; 10845 Kinsman Road, Newbury, OH 44065 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PARK, Stuart [US/US]; 13205 Stoney Springs Drive, Chardon, OH 44024 (US).

- (74) Agent: HLAVKA, John, R.; Watts Hoffmann Co., L.P.A., P.O. Box 99839, Cleveland, OH 44199-0839 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: FLUID TREATMENT SYSTEM



(57) Abstract: A control valve for a water treatment system which includes a turbine rotatably mounted within a water receiving chamber. A nozzle assembly communicates water from a water receiving chamber to the turbine in a driving relationship. The nozzle assembly defines first and second fluid paths, one of the flow paths may include a fluid pressure response valve element for controlling fluid flow along the one path. Alternate nozzle assemblies are also disclosed which include only one flow path. In these alternate constructions, vanes or louvers are defined within the throat and a blocking wall is used in one embodiment to reduce the effective inlet area of the throat. The disclosed nozzle assemblies are intended to be replacably held in the control valve and any one of the nozzle assemblies can be installed in the control valve to suit particular applications.



without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.